

APRIL 1974

GEORGE C. MARSHALL**SPACE
FLIGHT
CENTER**

DATA BOOK FOR 12.5-INCH DIAMETER
 SRB THERMAL MODEL WATER FLOTATION
 TEST - 14.7 PSIA, SERIES P020

NASA/MSFC

(NASA-TM-X-70405) DATA BOOK FOR 12.5-INCH
 DIAMETER SRB THERMAL MODEL WATER FLOTATION
 TEST: 14.7 psia, SERIES P020 (NASA) 305 p
 HC \$9.25

N75-18281

CSCL 22B

Unclassified

G3/15 12403

FLUID MECHANICS SECTION
 FLUID MECHANICS & DYNAMICS BRANCH
 PROPULSION & THERMODYNAMICS DIVISION
 ASTRONAUTICS LABORATORY

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION



TECHNICAL REPORT STANDARD TITLE PAGE


1. REPORT NO. M-ASTN-74-2	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE Data Book for 12.5-Inch Diameter SRB Thermal Model Water Flotation Test - 14.7 PSIA, Series P020		5. REPORT DATE	
7. AUTHOR(S) Steve L. Allums		6. PERFORMING ORGANIZATION CODE	
9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, AL 35812		8. PERFORMING ORGANIZATION REPORT #	
12. SPONSORING AGENCY NAME AND ADDRESS National Aeronautics and Space Administration Washington, DC 20546		10. WORK UNIT NO.	
		11. CONTRACT OR GRANT NO.	
		13. TYPE OF REPORT & PERIOD COVERED Data Book	
14. SPONSORING AGENCY CODE			
15. SUPPLEMENTARY NOTES Prepared by Astronautics Laboratory, Science & Engineering			
16. ABSTRACT This report presents data acquired from the initial series of tests conducted to determine how thermal conditions affect SRB (Space Shuttle Solid Rocket Booster) flotation. Included are acceleration, pressure, and temperature data recorded from initial water impact to final flotation position using a 12.5-inch diameter thermal model of the SRB at ambient pressure. The model was 136.9 inches long and weighed 117.3 lbm. Forty valid tests were conducted from July 19 to August 16, 1973. These tests indicated the following differences from ambient temperature tests:			
<ol style="list-style-type: none"> 1. Significant negative static pressures can occur during penetration. 2. Maximum penetration is increased. 3. Final flotation is in the spar buoy mode. 			
17. KEY WORDS thermal effects on water impact thermal effects on flotation rocket motor flotation flotation test data		18. DISTRIBUTION STATEMENT Unclassified-Unlimited  A. L. Worlund Chief, Fluid Mechanics & Dynamics Branch	
19. SECURITY CLASSIF. (of this report) UNCLASSIFIED	20. SECURITY CLASSIF. (of this page)	21. NO. OF PAGES 305	22. PRICE

TABLE OF CONTENTS

	PAGE	
SECTION I	INTRODUCTION	2
SECTION II	MODEL DESCRIPTION	3
SECTION III	TEST PROCEDURE	4
SECTION IV	DATA ACQUISITION AND INSTRUMENTATION	5
SECTION V	DATA PROCESSING AND EVALUATION	6
SECTION VI	DATA PRESENTATION	7
APPENDIX A	IMPACT PARAMETERS	A-i
APPENDIX B	TEST DATA	B-i

LIST OF ILLUSTRATIONS

<u>FIGURE</u>	<u>TITLE</u>	<u>PAGE</u>
1	SRB TEST MODEL	9
2	MODEL DIMENSIONS	10
3	MODEL COORDINATE SYSTEM AND PARAMETER DEFINITION	11
4	ACCELEROMETER LOCATIONS	12
5	PRESSURE TRANSDUCER AND TEMPERATURE THERMOCOUPLE LOCATIONS	13

LIST OF TABLES

<u>TABLE</u>	<u>TITLE</u>	<u>PAGE</u>
1	INSTRUMENTATION PROGRAM	8

SUMMARY

This report presents data acquired from the initial series of tests conducted to determine how thermal conditions affect SRB (Space Shuttle Solid Rocket Booster) flotation. Included are acceleration, pressure, and temperature data recorded from initial water impact to final flotation position using a 12.5-inch diameter thermal model (Figure 1) of the SRB at ambient pressure. The model was 136.9 inches long and weighed 117.3 lbm. Forty valid tests were conducted from July 19 to August 16, 1973. These tests indicated the following differences from ambient temperature tests:

1. Significant negative static pressures can occur during penetration.
2. Maximum penetration is increased.
3. Final flotation is in the spar buoy mode.

SECTION I. INTRODUCTION

This report presents processed acceleration, pressure, and photographic data recorded during water impact tests using a 12.5-inch thermal model of the Space Shuttle Solid Rocket Booster (SRB). These tests were conducted from July 19 to August 16, 1973. A description of the model, test procedure, instrumentation, and data acquisition systems is included.

These tests investigated thermal effects on a scale model SRB during impact, penetration, slapdown and final flotation at 14.7 psia by varying the model temperature at water entry. Entry dynamic conditions were varied by using different combinations of vertical velocities and water impact angles. Results from these tests will be used to develop analytical models for the full scale SRB and to indicate potential problem areas.

Forty valid drop tests were conducted.

SECTION II. MODEL DESCRIPTION

The test specimen was a model of the 142-inch diameter Space Shuttle SRB with a flared skirt and a full length nozzle. The model was a rigid body constructed of aluminum alloy 2219-T87 and contained three sections:

1. Cylindrical Section (four segments)
2. Motor Nozzle Section
3. Flared Skirt Section

The dimensions of the model (see Figure 2) were:

- o Length: 136.9 inches
- o Body Diameter: 12.5 inches
- o Skirt Diameter: 16.5 inches
- o Weight: 117.3 lbm
- o Pitch Mass Moment of Inertia: 34.9 slug-ft²
- o C.G. Location (aft of the nose plate): 74.0 inches

Geometric patterns were placed on the model to aid in photographic data reduction. Twenty-four heater strips with a rating of 720 watts were placed around the cylindrical section. Four heater strips (360 watts) were placed on the nozzle outside surface and two strips (120 watts) on the thrust cone. No heater strips were placed on the flared skirt. External insulation (Dow Corning Silicon Paint 93-027) was sprayed on the external surface of the model to a depth of .02 inch.

SECTION III. TEST PROCEDURE

Testing of the 12.5-inch diameter thermal model was conducted in the Over Water Launch (OWL) tank facility at Marshall Space Flight Center (MSFC). The model was suspended above the OWL tank by a quick release device at the specified initial angle. The model height above the water surface was varied to yield the specified impact velocities. After the model was in position for release, power was applied to strip heaters. When the model wall temperature reached the test temperature, the release mechanism was activated and the model was allowed to fall freely. The model impacted tail first with nominal vertical impact velocities of 5, 15, and 30 ft/sec. The nominal off-vertical pitch angles were 0°, 10°, and 20°. Average wall temperatures ranged from ambient to 450°F.

The procedure for drying out the inside of the model after each test was as follows:

1. With the model in a vertical position and the nozzle down, an air supply line was inserted three feet inside the model.
2. The model was heated to 300°F with the air supply operating for 10 minutes.
3. The air supply system was removed and the model was heated or cooled to the test temperature.

The test run number, nominal vertical velocity, initial impact angles and temperatures are shown in Appendix A. Figure 3 shows the coordinate system and defines the parameters used in the test program.

SECTION IV. DATA ACQUISITION AND INSTRUMENTATION

The data acquisition system consisted of acceleration, pressure, and strain gage transducers with their associated signal conditioning electronics, multiplexing equipment, and analog tape recording system. An oscilloscope recorder was used to display online measurements during each test drop.

Instrumentation consisted of six accelerometers, two ullage pressure transducers, two ullage and six wall mounted thermocouples. Measurement identification numbers, transducer types, and other pertinent instrumentation details are given in Table 1. Figures 4 and 5 show the instrumentation locations.

Five cameras were placed above and two below the water surface. Two camera systems were used. A high speed (250 frames/second) camera system filmed initial impact and slapdown. This system consisted of one camera above and one below the water level that sighted the impact point along the line of descent of the model into the water. A third high speed camera sighted the impact point from a position 90° away and below the water level. The second system had two low speed (24 frames/second) cameras that filmed the test from release of the model until final flotation mode. The cameras were located above the water level and 90° apart in a horizontal plane.

All data acquisition systems were calibrated in accordance with approved laboratory practices and calibrations were maintained as required.

SECTION V. DATA PROCESSING AND EVALUATION

Onsite data evaluation was performed after each drop. All oscilloscopes were reviewed to determine the validity of each measurement and time slices were selected for time history plots. Analog data tapes from each test were sent to MSFC Computation Laboratory for reduction. A digitized time history plot for each valid data channel was made with a sufficient time slice to include model release, water impact, slapdown, and rebound conditions. An additional time history plot was made for the pressure and temperature channels which extended these time history plots to a total time of 15 to 30 seconds.

SECTION VI. DATA PRESENTATION

Model impact parameters obtained from photographic data reduction are presented in Appendix A. Parameters included are:

- o Vertical impact angle (deg)
- o Maximum penetration depth (ft)
- o Vertical angle at maximum penetration (deg)

The impact velocities were calculated from accelerometer data which indicates release time and impact time.

Acceleration, pressure, and temperature data time history plots are presented in Appendix B. Acceleration (g), pressure (psig), and temperature ($^{\circ}$ F) are presented as a function of time.

TABLE 1. INSTRUMENTATION PROGRAM

<u>Measurement Number</u>	<u>Measurement Type</u>	<u>Frequency Response (Hz)</u>	<u>Full Scale Range</u>	<u>Sensitive Axis</u>
EP001	Accelerometer	2 - 400	\pm 25G	Pitch
EY002	"	"	"	Yaw
EA003	"	"	"	Axial
EP004	"	"	"	Pitch
EY005	"	"	"	Yaw
EA006	"	"	"	Axial
D0001	Pressure	"	\pm 12.5 PSIG	Internal
D0002	"	"	"	"
C0001	Thermocouple	"	500°F	External Wall
C0002	"	"	"	Internal Wall
C0003	"	"	"	Ullage
C0004	"	"	"	Internal Wall
C0005	"	"	"	Ullage
C0006	"	"	"	Internal Wall
C0007	"	"	"	"
C0008	"	"	"	Internal Wall

ORIGINAL PAGE IS
OF POOR QUALITY





FIGURE 1. SRB TEST MODEL

NOTE: DIMENSIONS IN INCHES



LONG NOZZLE

FIGURE 2. MODEL DIMENSIONS

11




FIGURE 3. MODEL COORDINATE SYSTEM AND PARAMETER DEFINITION




FIGURE 4. 12.5-INCH SRB THERMAL MODEL ACCELEROMETER LOCATIONS




FIGURE 5. 12.5-INCH THERMAL SRB MODEL PRESSURE AND TEMPERATURE LOCATIONS

APPROVAL

DATA BOOK FOR 12.5-INCH DIAMETER SOLID ROCKET BOOSTER
THERMAL MODEL WATER IMPACT TEST PROGRAM

by
S. L. Allums

The information in this report has been reviewed and approved
for technical accuracy.

L. J. Hastings

L. J. Hastings
Chief, Fluid Mechanics Section

A. L. Worlund

A. L. Worlund
Chief, Fluid Mechanics & Dynamics Branch

C. C. Wood

C. C. Wood
Acting Chief, Propulsion & Thermodynamics
Division

PRECEDING PAGE BLANK NOT FILMED

APPENDIX A

**IMPACT, PENETRATION AND
INITIAL TEMPERATURE DATA**

12.5-INCH THERMAL MODEL SRB

TABLE 1. IMPACT PARAMETERS

TEST NO.	IMPACT VELOCITY ft/sec	HORIZONTAL VELOCITY ft/sec	IMPACT ANGLE degrees	ANGLE AT MAXIMUM PENETRATION degrees	MAXIMUM PENETRATION ft / sec	AVERAGE WALL TEMPERATURE °F	
						TIME	ULLAGE TEMPERATURES
1	5.15	0	0.50	4.899	4.048 / 1.040		
2	15.70	0	0.10	3.999	4.775 / 0.684		
3	30.24	1.23	-0.10	1.0	5.970 / 0.624		
4	30.88	0	-9.20	-16.69	5.839 / 0.280		
5	15.74	0	10.70	32.49	4.348 / 0.592		
6	5.24	0	11.90	36.09	3.799 / 0.791		
7	3.06	0	19.60	44.69	3.263 / 0.764		
8	15.12	0	19.70	46.79	3.496 / 0.548		
9	30.88	0	19.80	47.19	4.327 / 0.384		
11	30.24	-0.99	0.90	0.90	6.536 / 0.560	213 / 245	
12	16.02	0	0.70	0.70	5.498 / 0.812	180 / 198	
13	4.99	0	-0.59	0.59	4.084 / 0.836	162 / 183	
14	15.67	0	19.10	47.39	3.817 / 0.528	212 / 240	
15	6.82	0	19.20	46.39	3.234 / 0.684	166 / 205	
16	30.18	0	18.20	49.19	4.472 / 0.412	195 / 245	
17	5.40	0	11.60	41.79	4.188 / 0.90	165 / 194	
18	15.28	0	11.00	37.99	4.522 / 0.676	185 / 204	
19	30.18	0	12.0	43.39	5.799 / 0.628	187 / 212	
20	4.34	0	-- NO DATA ----		4.52 / 1.04	190 / 236	
23	15.15	0	0.30	1.39	5.541 / 0.884	304 / 330	
24	4.99	0	0.10	0.10	4.183 / 0.968	283 / 319	

TABLE 1. IMPACT PARAMETERS (Cont'd)


TEST NO.	IMPACT VELOCITY ft/sec	HORIZONTAL VELOCITY ft/sec	IMPACT ANGLE degrees	ANGLE AT MAXIMUM PENETRATION degrees	MAXIMUM PENETRATION		AVERAGE WALL TEMPERATURE °F	ULLAGE
					ft	/ sec		
25	4.34	0	-0.10	1.30	3.932	/ 0.940	266 / 280	
26	30.40	0	0.40	3.89	6.288	/ 0.608	279 / 305	
27	30.50	0	0.80	3.89	7.344	/ 0.816	258 / 300	
28	30.30	0	0.60	2.99	6.992	/ 0.708	298 / 355	
29	15.25	-----	NO DATA	-----	4.92	/ 0.708	283 / 340	
31	30.11	0	20.10	27.89	2.40	/ 0.196	325 / 377	
32	15.18	0	0.70	0.79	4.510	/ 0.615	187 / 183	
33	4.05	0	-0.30	6.90	4.223	/ 1.096	224 / 253	
34	14.80	0	0.80	0.79	5.069	/ 0.776	353 / 408	
35	14.83	0	-0.30	0.80	5.126	/ 0.780	404 / 472	
37	15.06	0	18.70	46.49	3.447	/ 0.547	396 / 458	
38	14.77	0	0.20	0.50	5.141	/ 0.748	399 / 447	
39	14.80	0	0.10	0.29	5.138	/ 0.764	455 / 536	
40	23.58	0	0.70	2.69	6.274	/ 0.748	312 / 357	
42	23.81	-----	NO DATA	-----	7.25	/ .708	446 / 521	
43	23.81	0	18.399	52.89	4.228	/ 0.528	372 / 413	
44	35.97	0	18.70	26.29	3.332	/ 0.164	277 / 320	
45	36.03	1.13	1.70	4.89	7.635	/ 0.676	273 / 342	


APPENDIX B


ACCELERATION, PRESSURE, AND
TEMPERATURE DATA



APPENDIX B
TABLE OF CONTENTS


<u>Test Run No.</u>	<u>Page</u>
P020-1	B-1
2	B-5
3	B-9
4	B-13
5	B-17
6	B-21
7	B-25
8	B-29
9	B-33
11	B-37
12	B-45
13	B-52
14	B-59
15	B-67
16	B-75
17	B-83
18	B-91
19	B-99
20	B-106
23	B-114
24	B-123
25	B-133
26	B-143
27	B-153
28	B-163
29	B-172
31	B-181
33	B-190
34	B-198
35	B-206
37	B-214
38	B-222
39	B-230
40	B-238
42	B-246
43	B-251
44	B-259
45	B-267

















































SEQ. = 0503



































AMPLITUDE







AMPLITUDE

































B-34










AMPLITUDE


C0002

P020-9-1-40















4

A
M
P
L
I
T
U
D
E


5






SEG. = 510


AMPLITUDE






AMPLITUDE







AMPLITUDE





















4







5






















B-53



















12

A
M
P
L
I
T
U
D
EA
M
P
L
I
T
U
D
E

13









4




SEQ. = 0548






5



SEQ. = 0548














12







13




















4

A
M
P
L
I
T
U
D
EA
M
P
L
I
T
U
D
EA
M
P
L
I
T
U
D
E



5











12






13











1




C-2







AMPLITUDE






AMPLITUDE




AMPLITUDE













12







TEST 17 - DATA NOT AVAILABLE




PAGES B-84 THROUGH B-90
ARE LEFT OUT INTENTIONALLY









PRECEDING PAGE BLANK NOT FILMED


















12







13














4






AMPLITUDE






AMPLITUDE




5









12







13













1


SEQ. = 0515






11






11







11










3













5

SEQ. = 517







AMPLITUDE




1



AMPLITUDE












12










13



















5









7



























SEQ. = 519






















SEQ. = 519




SEQ. = 519















B-142













D0002

P020-26-1-48

A
M
P
L
I
T
U
D
E






SEQ. = 520


C0004 020-26-1-104 12.5 INCH THERMAL WATER RECOVERY RUN F020-26

AMPLITUDE




AMPLITUDE




C0005 020-26-1-112




AMPLITUDE

C0006 020-26-1-120












B-152


SEQ. = 521









4






AMPLITUDE




AMPLITUDE




AMPLITUDE







B-158




SEQ. = 521
C0004 020-27-1-104 12.5 INCH THERMAL WATER RECOVERY RUN P020-27







C0005 020-27-1-112




C0006 020-27-1-120



















2

















5










































9/20. # 0523
C0007 020-29-1-128 12.5 INCH THERMAL WATER RECOVERY RUN P020-29



















3




















19





SEQ. = 0525































12






SEQ. = 0528







SEQ. = 0528




AMPLITUDE




AMPLITUDE



AMPLITUDE




C0008 020-34-1-136




SEQ. = 0528

D0001 P020-34-1-40 12.5 INCH THERMAL WATER RECOVERY RUN P020-34




00002 P020-34-1-48




SEQ. = 0520


C0001 P020-34-1-80 12.5 INCH THERMAL WATER RECOVERY RUN P020-34



C0002 P020-34-1-88








C0003 P020-34-1-96





12

SEQ. = 0528









SEQ. = 0529

C0001

P020-35-1-80

12.5 INCH THERMAL WATER RECOVERY RUN P020-35

AMPLITUDE

400.

200.

0.00

1.00

2.00

3.00

4.00

5.00

TIME

C0002

P020-35-1-88

AMPLITUDE

400.

200.

0.00

1.00

2.00

3.00

4.00

5.00

TIME

C0003

P020-35-1-96

AMPLITUDE

400.

200.

0.00

1.00


2.00

3.00

4.00

5.00


TIME



C0008

P020-35-1-136

A
M
P
L
I
T
U
D
E




TIME

SEQ. = 0529

D0001 P020-35-1-40 12.5 INCH THERMAL WATER RECOVERY RUN P020-35

A
M
P
L
I
T
U
D
E




TIME

D0002

P020-35-1-48




A
M
P
L
I
T
U
D
E






TIME

SEQ. = 0529

C0001 P020-35-1-8D 12.5 INCH THERMAL WATER RECOVERY RUN P020-35





C0008

020-35-1-136

A
M
P
L
I
T
U
D
E

400.
200.

6. 8. 10. 12. 14. 16. 18. 20. 22. 24. 26. 28. 30. 32. 34.
TIME

SEQ. = 0529

C0001

F020-35-1-40 12.5 INCH THERMAL WATER RECOVERY RUN F020-35

A
M
P
L
I
T
U
D
E

2.
1.
0.
-1.

6. 8. 10. 12. 14. 16. 18. 20. 22. 24. 26. 28. 30. 32. 34.
TIME


D0002


F020-35-1-48


A
M
P
L
I
T
U
D
E


2.
1.
0.
-1.

6. 8. 10. 12. 14. 16. 18. 20. 22. 24. 26. 28. 30. 32. 34.
TIME











00008 020-37-1-136

A
M
P
L
I
T
U
D
E




SEQ. = 0530
00001 P020-37-1-40 12.5 INCH THERMAL WATER RECOVERY RUN P020-37


A
M
P
L
I
T
U
D
E




00002 P020-37-1-46

A
M
P
L
I
T
U
D
E







SEQ. = 0530
C0004 020-37-1-104 12.5 INCH THERMAL WATER RECOVERY RUN P020-37









C0005 020-37-1-112




C0006 020-37-1-120











SEQ. = 0531

P020-38-1-80 12.5 INCH THERMAL WATER RECOVERY RUN P020-38


AMPLITUDE




AMPLITUDE



AMPLITUDE






C0008

020-38-1-136

AMPLITUDE




1

AMPLITUDE

C0001


PG20-38-1-40 12.5 INCH THERMAL WATER RECOVERY RUN PG20-38




AMPLITUDE


00002

PG20-38-1-48







C0004 020-38-1-104 SEQ. = 0531
12.5 INCH THERMAL WATER RECOVERY RUN P020-38









C0005 020-38-1-112







C0006 020-38-1-120














C0008

020-39-1-136

AMPLITUDE

400.

200.

0.00

1.00

2.00

3.00

4.00

TIME

SEQ. = 0532

C0001

P020-39-1-40

12.5 INCH THERMAL WATER RECOVERY RUN P020-39

AMPLITUDE

2.

1.

0.

-1.

0.00

1.00

2.00

3.00

4.00

TIME

D0002

P020-39-1-48

AMPLITUDE

2.

1.

0.

-1.

0.00

1.00


2.00

3.00


4.00

TIME


SEQ. = 0532
C0001 P020-39-1-80 12.5 INCH THERMAL WATER RECOVERY RUN P020-39




C0002 P020-39-1-80




C0003 P020-39-1-96




SEQ. = 0532
C0004 020-39-1-104 12.5 INCH THERMAL WATER RECOVERY RUN P020-39



C0005 020-39-1-112



C0006 020-39-1-120



C0008

P020-39-1-136

AMPLITUDE

400.
200.

4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14.

TIME

SEQ. = 0532

AMPLITUDE

C0001 P020-39-1-49 12.5 INCH THERMAL WATER RECOVERY RUN P020-39

2.
1.
0.
-1.

4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14.

TIME

AMPLITUDE

D0002


P020-39-1-48

2.
1.
0.
-1.

4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14.


TIME

SEQ. = 0533




EA006

P020-40-1-56







EP001

P020-40-1-32









SEQ. = 0533









SEQ. = 0533










SEQ. = 0533






SEQ. = 0535

C0001

P020-42-1-80

12.5 INCH THERMAL WATER RECOVERY RUN P020-42


AMPLITUDE



AMPLITUDE

C0002


P020-42-1-88




AMPLITUDE

C0003

P020-42-1-96





SEQ. = 0535

C0001

P020-42-1-80

12.5 INCH THERMAL WATER RECOVERY RUN P020-42

AMPLITUDE

400.

200.

4.

5.

6.

7.

8.

9.

10.

11.

12.

TIME

C0002

P020-42-1-88

AMPLITUDE

400.

200.

4.

5.

6.

7.

8.

9.

10.

11.

12.

TIME

C0003

P020-42-1-96

AMPLITUDE

400.

200.

4.

5.

6.

7.

8.

9.

10.

11.

12.

TIME

SEQ. = 0535

C0004 020-42-1-104 12.5 INCH THERMAL WATER RECOVERY RUN P020-42

AMPLITUDE

400.
200.

4.

5.

6.

7.

8.

9.

10.

11.

12.

TIME

C0005

020-42-1-112

AMPLITUDE

400.
200.

4.

5.

6.

7.

8.

9.

10.

11.

12.

TIME

C0006

020-42-1-120

AMPLITUDE

400.
200.

4.

5.

6.

7.

8.

9.

10.

11.


12.

TIME

C0008

020-42-1-136

A
M
P
L
I
T
U
D
E




SEQ. = 0535

D0001

P020-42-1-40 12.5 INCH THERMAL WATER RECOVERY, RUN P020-42

5

A
M
P
L
I
T
U
D
E




TIME


D0002




P020-42-1-48


A
M
P
L
I
T
U
D
E




TIME









4






SEQ. = 0552


AMPLITUDE





AMPLITUDE




AMPLITUDE






12







13


























SEQ. = 0536


P020-44-1-80 12.5 INCH THERMAL WATER RECOVERY RUN P020-44



A
M
P
L
I
T
U
D
EA
M
P
L
I
T
U
D
EA
M
P
L
I
T
U
D
E


12



13















SEQ. = 0537


020-45-1-136 12.5 INCH THERMAL WATER RECOVERY RUN F020-45














4



5



SEQ. = 0537

